



# Handheld Thermocouple Thermometer

## CONTACT US

Phone: 310-830-6601

FAX: 310-830-9336

Email: info@sepor.com  
& services@sepor.com

## LOCATIONS

### WEST COAST

718 N. Fries Avenue  
Wilmington, CA 90744

### EAST COAST

3740 NW 124th Ave  
Coral Springs, FL 33065

## Description

These Digital Temperature Measurement Devices are easy to use and configured for basic temperature monitoring. They feature a 4 button sealed silicone rubber keypad, on/off switch, capture mode, °C or °F mode, single point calibration offset and calibration lockout. They operate on two "AA" batteries, included, with a minimum battery life of 500 hours and have a low battery indicator. The digital readout is a bright LCD display, and the meter is housed in polycarbonate plastic. Dimensions are 3.3" x 1.2" x 6.2" (H). Shipping Weight is 0.7 Lbs. Manufacturers warranty is 3 years from date of shipment. The thermocouple thermometer requires a probe to measure the temperature, These probes are convenient to use, detachable from the thermometer and have ANSI color coded mini conductors. The most common probe used is the general purpose probe, used for liquids, gases or semisolids. The sheath is 316 stainless steel. The maximum temperature is 1,372 °C. Read time is 6 seconds.



SEPOR #	DESCRIPTION	MODEL	TEMP RANGE	RESOLUTION/ ACCURACY
130C-010	Digital, Thermometer w/ K type, Thermocouple	3580	MINUS 250 to 1373C	0.1 C -1999.99 TO 999.9
130C-011	K Probe 5", 5' PVC, Coiled Cable	3582.2	MINUS 250 to 899C	0.1 C
130C-012	Protective, Integrative Stand	3580.3		
130C-013	Digital, Thermometer Kit Handheld, LCD Display Dual input jacks for K thermometers, For Type K,J,T,E probes	H 3564	MINUS 50 to 1093C	0.1C F/K <1000 1C F/K >1000
130C-014	Thermometer, traceable, F/C, switchable accepts all type K, J and T, probes, Computer compatible	HT 4007	MINUS 200 to 1370C	0.1 from -200 to 640C Accuracy +/- 1C