



# Laboratory Rotary Slurry Sampler WS-220

## CONTACT US

Phone: 310-830-6601

FAX: 310-830-9336

Email: [info@sepor.com](mailto:info@sepor.com)  
& [services@sepor.com](mailto:services@sepor.com)

## LOCATIONS

### WEST COAST

718 N. Fries Avenue  
Wilmington, CA 90744

### EAST COAST

3740 NW 124th Ave  
Coral Springs, FL 33065



### Description:

The WS-220 is a motorized slurry sampler for batch sampling of slurries with a top size particle of 3.5mm. A 20 liter (5 gallon) sample is quickly reduced to 2-1 liter representative samples. Each sample outlet gives 1/20th of the feed. The mixed bulk sample is introduced through a removable screen to a reservoir where the motorized turret head distributes reservoir discharge across machined cutters to deliver two accurate samples. Contact parts are stainless steel.

Accurately samples (2) one-twentieth (1/20) representative samples from larger sample of free-flowing slurry.

- Sampler can be used in manual or automatic sampling applications.
- Maximum particle size: 3.5 mm (0.132 inch).
- Unit is supplied complete with (2) one-liter sampling cups, trash screen and drive motor. (120 or 220 V, 50 or 60 Hz).

Catalog Number	Description	Dimensions (in.)	Shipping Weight
<b>040J-011</b>	115V/60Hz	30 x 30 x 50	200 Lbs.
<b>040J-012</b>	220V/50Hz	30 x 30 x 50	200 Lbs.